



## LP1364

TURNBUCKLES

### Material

Steel (C45, 1.0503), zinc-plated.  
Hot dip galvanized version, above M12 available on request providing increased protection against corrosion. Please add -

FZ for hot dip galvanized, e.g. LP1364.  
R008-FZ.

**Only suitable for use in tension.**

### Important Notes

**Turnbuckles are not to be used for lifting.**

Order No.	Thread hand	d <sub>1</sub>	d <sub>2</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	l <sub>4</sub>	w <sub>1</sub>	Weight kg
LP1364.R008	Right	M 8	8.5	125	116	68	28.75	9.0	0.095
LP1364.R010	Right	M10	8.5	139	130	82	29.25	10.7	0.132
LP1364.R012	Right	M12	10.5	160	150	90	44.75	15.5	0.215
LP1364.R016	Right	M16	12.5	186	172	102	45.25	20.0	0.405
LP1364.R020	Right	M20	17.0	205	185	115	59.50	23.5	0.812
LP1364.R024	Right	M24	20.5	240	215	125	62.75	29.0	1.395
LP1364.R030	Right	M30	25.0	290	255	150	89.50	34.0	2.690
LP1364.L008	Left	M 8	8.5	125	116	68	28.75	9.0	0.095
LP1364.L010	Left	M10	8.5	139	130	82	29.25	10.7	0.132
LP1364.L012	Left	M12	10.5	160	150	90	44.75	15.5	0.215
LP1364.L016	Left	M16	12.5	186	172	102	45.25	20.0	0.405
LP1364.L020	Left	M20	17.0	205	185	115	59.50	23.5	0.812
LP1364.L024	Left	M24	20.5	240	215	125	62.75	29.0	1.395
LP1364.L030	Left	M30	25.0	290	255	150	89.5	34.0	2.690