



SE0524

EXPANSION SEALING PLUGS

Material

Sleeve: case-hardened steel, black oxide finish.

Pin: heat-treatable steel, black oxide finish.

Technical Notes

To order please specify orifice size d_3

required (-xxx) and add to order no.

Ordering example:

Select the bore size and d_3 required (in inches).

eg. SE0524-070-030 is a 7mm pull plug restrictor with 0.030" orifice.

Important Notes

Please refer to technical pages for product installation details.

| Order No. | d_1 | l_1 | l_2 | d_2 +0.1 -0.0 | l_3 | d_3 inch | t |
|------------------|-------|-------|-------|--------------------|-------|---------------|-------------|
| SE0524.070-XXX-C | 7.0 | 13.0 | 7.5 | 7.0 | 8.0 | 0,012-0,13 | 4-40 UNC |
| SE0524.080-XXX-C | 8.0 | 14.0 | 8.5 | 8.0 | 9.0 | 0,012-0,15 | 6-32 UNC |
| SE0524.090-XXX-C | 9.0 | 16.0 | 9.5 | 9.0 | 10.0 | 0,012-0,17 | 8-32 UNC |
| SE0524.100-XXX-C | 10.0 | 18.0 | 10.5 | 10.0 | 11.0 | 0,012-0,20 | 10-32 UNC |
| SE0524.120-XXX-C | 12.0 | 21.0 | 12.5 | 12.0 | 13.0 | 0,012-0,24 | 10-32 UNC |
| SE0524.140-XXX-C | 14.0 | 25.0 | 14.5 | 14.0 | 15.0 | 0,012-0,28 | 1/4-20 UNC |
| SE0524.160-XXX-C | 16.0 | 28.0 | 16.5 | 16.0 | 17.0 | 0,012-0,30 | 1/4-20 UNC |
| SE0524.180-XXX-C | 18.0 | 31.5 | 18.5 | 18.0 | 19.0 | 0,012-0,35 | 5/16-18 UNC |
| SE0524.200-XXX-C | 20.0 | 35.0 | 20.5 | 20.0 | 21.0 | 0,012-0,40 | 3/8-16 UNC |
| SE0524.220-XXX-C | 22.0 | 38.5 | 22.5 | 22.0 | 23.0 | 0,012-0,43 | 3/8-16 UNC |